



Cordless Chain Saw

DUC204 / DUC254 / DUC254C

200 mm (8") 250 mm (10") 250 mm (10")



Lightweight & High Speed Chain Efficiency equivalent to 23mL class engine chain saw



Photo: DUC254

18V
LITHIUM-ION

BL
MOTOR

Sprocket nose bar

DUC254
250 mm (10")

DUC204
200 mm (8")



Solid carving bar

DUC254C
250 mm (10")



Max. chain speed

24 m/s

Saw chain: 90px or 91px

Efficiency equivalent

BL
MOTOR

High operating efficiency

Outer Rotor Brushless Motor direct-drive system provides high operating efficiency



Hanging D-ring

Up to 23mL class engine chain saw

y
ive
ency.



High operability

Chain brake and Variable speed trigger switch provide high operability equivalent to engine chain saw.



Net weight

3.1 kg

with BL1850B
Guide Bar 200mm
Saw Chain 90XP



Cutting work amount

Work volume on a single full battery charge

About 160 cuts



- 50mm cedar timber
- saw chain : 90PX
- Battery : BL1850B

Captive nuts

prevent loss of nut when removing sprocket cover to replace guide bar or saw chain.

Highly efficient cutting

Direct drive of High output BL motor provides high saw chain speed; enabling to cut a workpiece without pushing hard.

- 15% faster than current 22.2mL engine model in cutting a 50mm x 50mm square wood

Torque boost mode

Torque boost mode provides more power for cutting thick branches or hard branches.

- 50% faster than current 22.2mL engine model in cutting a 100mm x 100mm square wood
- It cannot be used when BL1815N or BL1820B is installed.



*Push main power switch for a few seconds until the main power lamp lights up in yellow



Main power switch with auto power-off function



Metal chain catcher



Excellent tool balance



Adjustable automatic chain lubrication



Variable speed trigger switch



Chain oil level window

XPT

Extreme Protection Technology



Blower
DUB362 /
DUB361

Pruning Shear
DUP361

Grass Trimmer
DUR365U / DUR364L
DUR366L

Hedge Trimmer
DUH483 / DUH523

Recipro Saw
DJR185 /
DJR183

String
Trimmer
DUR181

Chain Saw
DUC252 / DUC252C
DUC400 / DUC353
DUC303 / DUC302

Hedge Trimmer
DUH651 /
DUH551

Multi Function
Power Head
DUX60

Grass Shear
DUM604

Chain Saw
DUC122 / DUC254 /
DUC204 / DUC254C

Wheelbarrow
DCU180

Garden
Sprayer
DVF154 /
VF104

Lawn Mower
DLM380 /
DLM431



1.5Ah 2.0Ah
3.0Ah 4.0Ah
5.0Ah 6.0Ah

Accessories

Guide Bar / Saw Chain / Guide Bar Cover

Cutter type: MC : Micro chisel, CC: Chamfer chisel

Guide Bar				Saw Chain						Bar Cover	Drive sprocket	
Bar length	Motor Mount	Type	Part No.	No. of drive links	gauge	pitch	Type OREGON / DOLMAR	Cutter type	Part No.	Part No.	Type	Part No.
25cm/10"	----	Solid carving bar	168407-7	60	1.3mm/.050"	1/4"	25AP / 466	MC	194098-8	452093-7	Sprocket	198259-2
20cm/8"	A041	Sprocket nose bar	161848-6	33	1.1mm/.043"	3/8"LP	90PX / 291	CC	199076-3	458503-2	Sprocket	199063-2
25cm/10"	A041	Sprocket nose bar	161846-0	40					199075-5	452093-7		
25cm/10"	A041	Sprocket nose bar	168408-5	40	1.3mm/.050"	3/8"LP	91PX / 492	CC	196205-9	452093-7		

File and File holder

For Model : Chain saw *with gurip



Saw chain type	Size	File	File and File holder
		Part No.	Part No.
25AP, 91PX, 91VLX, 466, 492, 196	4mm	*744003-1	----
		D953003090	195089-2 D953030010
90PX, 33SL, 34SL, 291	4.5mm	D953003100	195923-6 D953030020

File handle, Flat file & Depth gauge jointer

For all saw chain



File handle	Flat file	Depth gauge jointer
Part No.	Part No.	Part No.
D953004010	D953003060	D953100090

Chain oil

Size	Part No.
100mL	182229-1
1L	195093-1 D988002656
5L	D988002658

BIOTOP Chain oil

Size	Part No.
1L	D980008610
5L	D980008611

Spike bumper



Part No.
199067-4

Cordless Chain Saw

DUC204 200 mm / DUC254, DUC254C 250 mm (10")

	DUC204	DUC254	DUC254C
Variable Speed	Guide Bar Length 200 mm (8")	250 mm (10")	250 mm (10") (Carving Bar)
Brake	Chain Pitch / Chain Gauge 3/8" / 1.1 mm (0.043")	3/8" / 1.1 mm (0.043")	1/4" / 1.3 mm (0.050")
Soft Start	Chain Speed 0 - 24 m/s (0 - 1,440 m/min) (0 - 4,720 FPM)	0 - 24 m/s (0 - 1,440 m/min) (0 - 4,720 FPM)	0 - 22.5 m/s (0 - 1,350 m/min) (0 - 4,430 FPM)
	Chain Oil Tank Volume 140 mL	140 mL	140 mL
	Sound Pressure Level 92.2 dB(A)	92.2 dB(A)	92.2 dB(A)
	Sound Power Level 103.2 dB(A)	103.2 dB(A)	103.2 dB(A)
	Vibration Level Cutting Wood: 3.1 m/s ²	Cutting Wood: 3.1 m/s ²	Cutting Wood: 4.1 m/s ²
	Dimensions (L x W x H) w/o Guide Bar: 258x184x191 mm (10-1/8"x7-1/4"x7-1/2")	w/o Guide Bar: 258x184x191 mm (10-1/8"x7-1/4"x7-1/2")	w/o Guide Bar: 258x184x191 mm (10-1/8"x7-1/4"x7-1/2")
	w/ 20 cm (7-7/8") 90PX Sprocket Nose Bar: 417x184x191 mm (16-3/8"x7-1/4"x7-1/2")	w/ 25 cm (10") 90PX Sprocket Nose Bar: 482x184x191 mm (19"x7-1/4"x7-1/2")	w/ 25 cm (10") 25AP Carving Bar: 496x184x191 mm (17-1/2"x7-1/2"x7-1/4")
Standard Equipment:	Net weight 2.8 - 3.1 kg (6.2 - 6.8 lbs.)	2.8 - 3.2 kg (6.2 - 6.9 lbs.)	2.9 - 3.3 kg (6.3 - 7.3 lbs.)

Saw Chain, Guide Bar, Guide Bar Cover, Wrench, Accessory Bag, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201803