



Petrol Hedge Trimmer

Satisfy Professional's Needs

EH5000W 500mm, EH6000W 600mm, EH7500W 750mm (Double-sided blade)
EH7500S 750mm (Single-sided blade)

Extra Light Design
with Anti-vibration system

22.2
mL

Double-sided blade
EH5000W, EH6000W, EH7500W



Single-sided blade
EH7500S

Environment-friendly 2-stroke engine

developed in compliance with: CARB Tier 3, EPA Phase 2, EU Stage 2, Safety regulations of the EC Directives

Approx.
50
hours

Longer lubrication cycle
obtained by circulating grease
in gear housing
Competitors' models and our current
models: approx. 20 hours

Photo:
EH7500W

5-Position rotating
rear handle

Ergonomically angled
and contoured grip of
rear handle

Photo:
EH7500S

Forward exhaust direction

EH5000W: 500mm, EH6000W: 600mm, EH7500W: 750mm

EH7500S: 750mm

Anti-vibration System

Equipped with floating structure of engine section and handle section for anti-vibration; four damper springs absorb vibration from engine to integrated front and rear handles.



Blade Teeth with 3 Sharpened Edges

Stain-free shear blade surface of glittering silver obtained by non-electrolyzed nickel plating that features high anti-abrasion surface for long lasting coating



Sap on the blade
(after 10 hour trimming of Boxwood)



Stain-free Blade



Our Current models

5-Position Rotating Rear Handle

(EH5000W, EH6000W, EH7500W)

can be locked at 0 degree and 45/ 90 degrees left and right for vertical or angled trimming.



Accessories

Blade Assembly

Double-sided Blade

for EH5000W Part No. 195820-6
for EH6000W Part No. 195821-4
for EH7500W Part No. 195822-2

Single-sided Blade

for EH7500S Part No. 195823-0

Chip receiver assembly set


for EH7500S
Part No. 195321-4



Toothed edge

designed like saw teeth can catch and prevent leaf or twig debris from falling over the edge of chip receiver.

Anti-side ribs
on the bottom plate prevents leaf or twig debris from sliding and slipping out of chip receiver.



Petrol Hedge Trimmer

- Anti Vibration
- Primer Pump
- Electronic Ignition



	EH5000W	EH6000W	EH7500W	EH7500S
Blade type	Double-sided	Double-sided	Double-sided	Single-sided
Blade length	500mm (19-3/4")	600mm (23-5/8")	750mm (29-1/2")	750mm (29-1/2")
Displacement	22.2mL	22.2mL	22.2mL	22.2mL
Engine power	0.68kW (1.0PS)	0.68kW (1.0PS)	0.68kW (1.0PS)	0.68kW (1.0PS)
Fuel mixture	50 : 1	50 : 1	50 : 1	50 : 1
Fuel tank	0.4L	0.4L	0.4L	0.4L
Dimensions (L x W x H)	1,014 x 262 x 216mm (40" x 10-3/8" x 8-1/2")	1,119 x 262 x 216mm (44" x 10-3/8" x 8-1/2")	1,259 x 262 x 216mm (49-1/2" x 10-3/8" x 8-1/2")	1,150 x 323 x 212mm (45-1/4" x 12-3/4" x 8-3/8")
*Net weight	4.8kg(10.5lbs)	5.0kg(11.0lbs)	5.2kg(11.4lbs)	4.7kg(10.4lbs)
Standard Equipment	Blade Cover, Socket Wrench, Hex Wrench			

*Dry weight Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BB-AF