


Cordless Combination Hammer DHR182 18 mm (11/16") Adapted for SDS-PLUS bits



Adapted for

SDS-PLUS bits













Depth gauge

can be adjusted for desired drilling depth simply by pushing single push button

Max Bit length

165_{mm}

(with DX05

Dust collection inlet

can be adjusted according to bit length simply by pushing single push button



by turning the dial, the dust falls off from the filter







Large dust box cover

can be opened simply by pushing single push button for easy dust cleaning.



makita





Twin LED job light





Excellent drilling performance

- Concrete with compressive strength of 40N/mm²
- Diameter: Ø10.5mm(3/8"), depth of 60mm(2-3/8")



Work Speed

70 %UP

compared to our predecessor model

Work Volume

30 %UP

compared to our predecessor model

Work Amount

About 80 pcs.

Battery: BL1850



Auto - start Wireless System

Wireless Unit

(option)

198901-5, 198900-7(EU), 199393-1(Asia)





Switch on the



Vacuum cleaner is activated



Accessories

Dust collection system



Dust cup

Part No. 198362-9 use with Grip base set Part No. 194581-5

Dust case

Part No. 199595-9



HEPA Filter

Part No. 199596-7



Cordless Combination Hammer

Variable Speed





Torque Limiter



Dust Collection
Built-in Job Light

Constant Speed



Standard Equipment: Dust Cup (country-specific), Side Grip, Depth Gauge, Battery, Charger

DHR182 18 mm (11/16") Adapted for SDS-PLUS bits

Impact Energy

Capacity

nergy EPTA-Procedure 05/2009: 1.7 J
Our experimental conditions: 1.6 J
Concrete: 18 mm (11/16")
Core Bit: 35 mm (1-3/8")
Diamond Core Bit (Dry Type): 32 mm (1-1/4")

No Load Speed (RPM) 0 - 1,350 Max Output 450 W Vibration Level Hammer

Sound pressure Level
Sound power Level
Dimensions (L x W x H)

Dimensions (L x W x H)

Net weight

Hammer Drilling into Concrete: 11.0 m/s² Drilling Into Metal: 2.5 m/s² or less 89 dB(A) 100 dB(A)

(LxWxH) w/BL1830B/BL1840B/BL1850B/BL1860B: 301x82x285 mm(11-7/8"x3-7/4"x11-1/4") 2.4 - 3.2 kg (5.3 - 7.0 lbs.)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan