



Cordless Fan CF003G 40Vmax / 18V / AC



XGT
40V **Li-ion**
max

18V
LITHIUM-ION

450 mm fan diameter



- Compatible with
- 40Vmax XGT Li-ion battery
 - 18V LXT Li-ion battery
 - AC (through AC adapter)





Front fan cover has been redesigned to supply air widely around the appliance therefore, this model is suited for air blowing or ventilation in a large place such as factory, warehouse, etc.

Max air flow volume
120 m³/min


Max air speed*
300 m/min
*Measured at 1.0 m away from the appliance

Compatible with 40Vmax / 18V Li-Ion battery / AC



XGT battery and LXT battery can be installed simultaneously.

Stepless air flow volume setting



Dial-style air flow volume adjustment (38 - 120m³/min)

Can be mounted onto MAKPAC cart



Portability can be enhanced by mounting the appliance onto MAKPAC cart.

Manual angle adjustment of fan head



90° up/45° down with a locking knob

Automatic oscillation



Automatic oscillation angle adjustment: 60°, 90°, 120° left/right

Accessory case



Located on the front of the appliance for storing AC adaptor, etc.



Continuous use (approx)

on a full battery charge [at Max air speed]

Battery	Without oscillation	With oscillation
BL1860B	90 min	85 min
BL4040	115 min	110 min
BL4080F	230 min	220 min



Three Off timer settings
1 hour, 2 hours, 4 hours

Charging Time

Model	Fast Charging		Model	Fast Charging	
	DC40RA	DC40RC		DC18RC	DC18SD
BL4020 2.0Ah	22 min	30 min	BL1815N 1.5Ah	15 min	30 min
BL4025 2.5Ah	28 min	38 min	BL1820B 2.0Ah	24 min	45 min
BL4040 4.0Ah	45 min	67 min	BL1830B 3.0Ah	22 min	60 min
BL4050F 5.0Ah	50 min	85 min	BL1840B 4.0Ah	36 min	90 min
BL4080F 8.0Ah	76 min	170 min	BL1850B 5.0Ah	45 min	110 min
			BL1860B 6.0Ah	55 min	130 min

not covered by EPTA-Procedure
Items of standard equipment and specifications may vary by country or area.

Cordless Fan

CF003G 40Vmax / 18V / AC

Variable Speed	Air velocity	96-300 m/min
	Air flow	38-120 m ³ /min
	Fan diameter	450 mm (17-3/4")
	Fan head angle adjustment	Up: 90° / Down: 45° Left: 90° / Right: 90°
	Automatic oscillation	Left: 60, 90, 120° Right: 60, 90, 120°
	Continuous use (min.) w/o oscillation	w/BL4040: 115 / w/BL4080F: 230 / w/BL1860B: 90
	Continuous use (min.) w/ oscillation	w/BL4040: 110 / w/BL4080F: 220 / w/BL1860B: 85
	Dimensions (L x W x H)	w/o Battery: 312 x 633 x 770 mm (12-1/4 x 25 x 30-1/4")
	Net weight	w/o Battery: 7.9 kg (17.4 lbs.)

Standard Equipment : AC adaptor

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202307