

Satisfy Professional's Needs



# Cordless Circular Saw HS011G 260 mm (10-1/4") / 270 mm (10-5/8")



# 40V Li-ion max



Lightweight  
with BL4050F

# 6.1 kg

Max cutting depth  
with 270mm saw blade

# 101 mm

**Work amount**  
on a single full battery charge  
Melapi (Thickness: 90mm /  
Width: 1,000mm / Bevel angle: 0°)  
with BL4050F

# 40 cuts



# High power and lightweight design

**BL MOTOR**

Rotatable dust nozzle

**Sub base**  
Sub base can be used as Guide rule by turning up side down.



**(BRAKE) Electric brake**

**Magnesium diecast**  
Base plate, Safety cover and Blade case

**Compatible with guide rail without adapter**  
providing precision cutting

**Twin LED Job light**  
with pre-glow and after glow functions



**Bevel cuts up to 1° left and 60° right.**



**Constant speed control**  
minimizes reduction in rotation speed under load, keeping operation efficiency.

**AWS Auto-start Wireless System**

The wireless activation function enables clean and comfortable operation. By connecting a supported tool to the cleaner, you can run the cleaner automatically along with the switch operation of the tool.



Wireless unit is compatible with all supported tools

**XPT eXtreme Protection Technology**

## Accessories

**Specialized EFFICUT blade**

**EFFICUT**




Size (mm)	Part No.
260x 2.15 x 25 x 24T	E-07733
270 x 2.15 x 25.4 x 24T	E-12974

**Guide rail**



Overall length (m)	Part No.
1	199140-0
1.4	194368-5
1.5	199141-8
1.9	194925-9
3	194367-7

**Clamp set**



Part No. type A: 194385-5  
type B: 199826-6

**Bevel guide set**



Part No. 196664-7


**Guide rail bag**



For 1.0m Guide rail  
Part No. E-05670

For 1.4m, 1.5m  
Guide rail  
Part No. E-05664

**Guide rail Joint connector 2pc set**



Part No. 198884-9  
198885-7(EU)

## Charging Time

	Fast Charging	
	DC40RA	DC40RC
<b>BL4020</b> 2.0Ah	<b>22 min</b>	<b>30 min</b>
<b>BL4025</b> 2.5Ah	<b>28 min</b>	<b>38 min</b>
<b>BL4040</b> 4.0Ah	<b>45 min</b>	<b>67 min</b>
* <b>BL4050F</b> 5.0Ah	<b>50 min</b>	<b>85 min</b>
* <b>BL4080F</b> 8.0Ah	<b>76 min</b>	<b>170 min</b>

\*1 Recommended battery

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

## Cordless Circular Saw

**HS011G 260 mm (10-1/4") / 270 mm (10-5/8")**

Brake	Hole Diameter	15.88, 25, 25.4, 30 mm (5/8, 1")
Constant Speed	Max Cutting Capacity	0°: 97 - 101 mm (3-13/16 - 4") 45°: 68 - 71 mm (2-11/16 - 2-13/16") 60°: 48 - 51 mm (1-7/8 - 2")
Soft Start	No Load Speed (RPM)	3,500
Dust Collection	Vibration Level	2.5 m/s <sup>2</sup> or less
Built-in Job Light	Sound Pressure Level	93 dB(A)
	Sound Power Level	104 dB(A)
	Dimensions (L x W x H)	w/ BL4020 / BL4025 / BL4040 / BL4050F or w/o Battery: 453 x 196 x 336 mm (17-7/8 x 7-3/4 x 13-1/4") w/ BL4080F: 453 x 214 x 336 mm (17-7/8 x 8-3/8 x 13-1/4")
	Net weight	5.5 - 6.7 kg (12.1 - 14.8 lbs.)

Standard Equipment : TCT Saw Blade, Sub Base, Hex Wrench, Battery, Charger

**Makita Corporation**

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202308